

BioPass FID02 Plus K49 & K50 User Manual



BioPass FIDO Plus K49

Dimension: **52mm x 19mm x 6.4mm**

Physical Interfaces: **USB Type-C**

Operating Temperatures: **-10°C - 50°C (14°F - 122°F)**



BioPass FIDO Plus K50

Dimension: **58mm x 19mm x 7mm**

Physical Interfaces: **USB Type-A**

Operating Temperatures: **-10°C - 50°C (14°F - 122°F)**

FIDO

The FIDO interface supports both FIDO2 and U2F, which presents as a generic human interface device (HID). The FIDO interface is supported on all desktop platforms running WebAuthn-compatible browsers or applications, as well as on Android and iOS (starting in iOS 13).

For more information of management of FIDO, please visit: <https://fido.ftsafe.com/fido-related/>.

PIV (Smart Card compatible)

BioPass FIDO Plus provides a PIV-compatible smart card application. PIV, or FIPS 201, is a US government standard. It enables RSA or ECC sign/encrypt operations using a private key stored on a smart card.

Default Value

- PIN: 123456
- PUK: 12345678
- Management Key (3DES): 313233343536373831323334353637383132333435363738

For more information of management PIV, please visit: <https://fido.ftsafe.com/piv-related/>.