

ePass2003

PKI Authentication Token



Email Signature and Encryption

Windows Smart Card Logon

Document Digital Signature

Secure Online Transaction

Disk and File Encryption

Remote VPN Access



FEITIAN
WE BUILD SECURITY

FEITIAN ePass2003 is a high security PKI based USB token incorporating the most powerful cryptographic technology and standards available today. It is designed for all Public Key Infrastructure environments and brings two-factor cryptographic authentications to applications where security is critical. FIPS 140-3 validated card operating system on-board key management mechanism enable a higher level of security assurance to wide range of sensitive applications. With combined compatibility of Microsoft Minidriver and OpenSC, the ePass2003 is compatible with applications running on Windows, Linux and Mac and therefore is the ideal choice for all industries requiring high level protection such as government, enterprise, financial institutions and media companies.

Enterprise

Corporations need not only keep networks secure but also digitally sign documents and emails. Instead of using several devices the ePass2003 does it all. The ePass2003 works with Microsoft Office for signing documents and also smart card logon and range of VPN vendors such as CheckPoint VPN to ensure your network is safe and secure. With support for both CSP and PKCS#11 interfaces you can be sure that ePass2003 works with your application.

Publishing and Media

In the world of publishing and media, getting media delivered to customers securely is key in order to safeguard ROI. With support for Windows EFS, PGP and other major file encryption formats media can be distributed quickly and easily online and offline without worrying about copyright theft. The ePass2003 also supports all major internet browsers such as Microsoft Edge, Firefox, Chrome, Safari and Internet Explorer to ensure your media reaches the widest possible audience. We also have tools to manage certificate including import, export and delete.

E-Government

The ePass2003 is a token of high standards. Compliant with FIPS 140-3 and Common Criteria EAL 5+ (chip level), ePass2003 is perfect for government solutions such as the declaring of taxes and judiciaries. In today's digital age where governments are moving towards a paperless workflow in order to reduce costs, help protect the environment and increase efficiency, the ePass2003 is the perfect replacement for written signatures.

Finance

In finance trust is king. In order to ensure the finances of millions of customers around the world, using a token that boasts the highest security on the market is key. With RSA, ECC and AES high security algorithms the customer's online transfers can be secured. With support also for SSL connections, the industry standard in secure online connections, there is always a secure connection every time. The ePass2003 is flexible due to its large memory, which allows the token to store many certificates and therefore be used with multiple accounts and applications.

Specifications

Supported operating systems	Windows / Linux / macOS / Android / iOS / iPadOS	Cryptographic algorithm	Asymmetric Key: PKCS#1 V2.2 Onboard Key Pair Generation RSA 2048/3072/4096 bits (RSAES-OEAP, RSASSA-PSS)	Physical parameters	Secure Chip: 32 bits high-performance Memory Space: 64 KB Connectivity: USB 1.1/2.0/3.0 compliant Standards: CE, FCC, RoHS Data Retention: at least 10 years
Hardware interface	ISO 7816-1, 2, 3, 4 compliant, CCID		Key Generation Time: For RSA 2048/3072: Seconds For RSA 4096: less than a minute ECC P-256, P-384, P-521		Flash Memory: Up to 4MB, enable autorun function
API standards	PKCS# 5, 7, 8, 10, 11, 12 Supported Cryptographic Service Provider (CSP) Microsoft Smart Card Minidriver Microsoft CNG, PC/SC, X.509 v3 certificate storage, SSL v3, IPSec/IKE, CSR Export		Symmetric Key: AES 128/192/256 bit		USB Connectors Durability: ≥2,500 plug-unplug cycles
Certification	FIPS 140-3 Level 3 Certified		Digest: SHA-256, SHA-384, SHA-512, SHA512/224, SHA-512/256		Operating: 0°C~50°C Storage: -20°C~60°C Humidity: 0~100% RH