





Micro USB, Bluetooth Class 2.1 + EDR $\leftarrow \rightarrow$ & Bluetooth 4.2 BLE



MSR + IC CARD + NFC + SCREEN + PIN PAD



Flexible Hardware / Module Customization













Made in Chir

2

5

8

0

4

7

3

6

9

#

Restaurant

Hotel



Gas station

ePayPOS600

SPECIFICATIONS

Memory	128KB RAM, 4MB FLASH
Processor	32-bit RISC Core
NFC	EMV3.0, 13.56MHz, ISO/IEC 14443, ISO18092, Type A&B Mifare card
MSR	ISO-7811, ISO-7813, bi-directional tracks 1, 2 & 3
IC	EMV 4.3, ISO-7816 T=0 & T=1, Class A/B/C
Display	Monochrome 128 × 64 pixels LCD
Keypad	5 × 3 PIN pad 15 keys
Connectivity	BR/EDR + BLE4.2
Battery	Li-ion battery 500 mAh / 3.7V
Charging	Via Micro USB connection to mobile phone / tablet / PC, or via compatible micro USB Plug Top Power Supply
Dimensions	59 mm(L) × 14 mm(W) × 113.6 mm(H)
Weight	105g
Environmental	Working temperature: 0 °C ~ +45 °C / 5 ~ 95% RH Storage temperature: –10 °C ~ +60 °C / 5 ~ 95% RH
Certification	PCI,EMV L1,EMV CL1,EMV L2,TQM Paywave, Paypass, Amex, Discover, Pure, QUICS, CE, FCC,BIS UN38.3,MSDS



FEITIAN Technologies Co., Ltd. www.ftsafe.com/payment