

# P30 Desktop Printer



High-speed output



POS & PC & WiFi connection



Application & high compatibility



Multi-interface design



Intelligent connection



Retail



Supermarket



Restaurant



Hotel



Parking lot



Gas station

# P30

## Desktop Printer

## SPECIFICATIONS

<b>Printing Technology</b>	Thermal line printing
<b>Print Width</b>	48-80±0.5mm
<b>Print Density</b>	576 points/line or 512 points/line
<b>Print speed</b>	300mm/s
<b>Print Interface</b>	USB+LAN+RS232 USB+RS232+BT (Optional) USB+RS232+WIFI (Optional)
<b>Media Dimensions</b>	80mm: 79.5 ± 0.5 x 83mm 58mm: 57.5 ± 0.5 x 83mm
<b>Thickness</b>	0.06 -0.08 mm
<b>Print Direction</b>	Upward Paper Feeding or Forward Paper Feeding
<b>Print Fonts</b>	ANK, Font A: 1.5×3.0mm(12×24) Font B: 1.1×2.1mm(9×17) Simplified/Traditional: 3.0×3.0mm(24×24)
<b>Barcode</b>	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) / CODE39/ITF/CODABAR/CODE93/CODE128 QRCODE/PDF417
<b>Cutters</b>	AutomaticCutter: Half-Cut
<b>Data Buffer</b>	Input Buffering: 2048k bytes NV Flash: 256k bytes
<b>Power adapter</b>	Input: AC100-240V, 50~60Hz Output: DC24V/2.5A Cash drawer output voltage: DC24V/1A
<b>Operating Systems</b>	Microsoft® Windows/Linux
<b>Dimensions(Weight)</b>	133*126*130mm/1.115 kg
<b>Working environment</b>	Temperature: 0°C~45°C, Storage Temperature: -10~60°C , Relative Humidity:10~90%
<b>Certifications</b>	CE

