

F600

Android Payment PAD



Android 9



4G + 3G + 2G
WiFi 2.4G/5G
BT 4.2



8" HD LCM
8MP + 5MP Cameras



MSR + IC + NFC + QR



Retail



Supermarket



Restaurant



Hotel



Parking lot



Gas station

F600

SPECIFICATIONS

Operating System	Android 9
Processor	Octa-Core, 8×1.8G, A53
Memory	RAM: 2GB/ROM: 16GB
Communications	4G (LTE-FDD/LTE-TDD) + 3G (WCDMA) + 2G (GSM/GPRS), WiFi 2.4GHz/5GHz, BT4.2 (BR/EDR+BLE)
Location	GPS, Beidou, GLONASS
Display	8 inch, 1280×800, IPS
Cameras	Rear: 8MP AF with Flash LED Front: 5MP FF
Battery	3.8V/8000mAh
Magnetic Card Reader	ISO/IEC 7811, ISO/IEC 7813, Track 1/2/3, Bi-directional swiping
IC Card Reader	ISO/IEC 7816, Conform to EMV L1/L2
NFC	13.56MHz, ISO/IEC 14443, ISO18092, Type A&B, Felica, Mifare card
Keys / Buttons	Power Key, Volume +/-, Function Key
Card Slot	SIM*2 + PSAM*1
Peripheral Ports	Type C*1(USB2.0, OTG)
Adapter	Input: 100-240V AC, 50/60Hz 0.35A Output: 5V DC/2.0A
Physical	251mm (L) × 136mm (W) × 15.8mm (H)
Weight	705g
Environment	Operating Temperature: -10°C ~ 50°C (14°F~122°F) Storage Temperature: -20°C ~ 60°C (-4°F~140°F) Relative Humidity: 5%-96% (Non-Condensing)
Accessories	Adapter*1, USB Cable(only charging)*1, Manual*1, Ejection Pin*1
Certifications	PCI, EMV L1&L2, EMV CL L1, Amex, Paywave, Paypass, Discover, JCB, Pure, QUICS, TQM(TBD), DGM&UN38.3&MSDS CE, GSMA, WEEE, NTRA-VOC

Optional Items

Network

SKU2(NA)
LTE-FDD: B2/4/5/7/12/13/17/25/26/66
LTE-TDD: B41
WCDMA: B2/4/5

Memory

RAM: 4GB/ROM:64GB

Camera

Front Camera: 2MP or none
Rear Camera: 5MP/FF/AF, 2MP/FF

USB Cable

Type C (data/damping)

Charging Cradle

5V/2A

Card Slot

PSAM*1 + SIM*1 + TF*1

Fingerprint

Biometric fingerprint module

Type C USB to RJ 45 Adapter

100 Mbps Ethernet LAN

Ports

Multi-Drop Bus Back clip
Dimension: 95.6*95.6*22mm

Screen Protector

Hydrogel film

Silicone Cover

Customized colors

POS Bracket

Desktop rotating bracket
Wall-mounted rotating bracket

F600 Options and Accessories



F600 FP Fingerprint

Dimensions(L*W*H)	251 × 136 × 15.8mm
Image Size	256*360 Pixels
Image Resolution	508 dpi
Sensor Type	Semi-conductive capacitive

Desktop Rotating Bracket



Vertical Angle	75°
Horizontal Angle	270°

Wall-mounted Rotating Bracket



Up and Down Tilt Angle	+35° / -50°
Left and Right Rotation Angle	180°

Charging Cradle



Screen Protector
Hydrogel film



Silicone Cover
Customized colors



Type C to RJ 45 Adapter
100 Mbps Ethernet LAN