

# F100

# **Non Payment Terminal**



Android 11



4G + 3G + 2G Wi-Fi 5: 2.4&5GHz BT 5.0



5.0" HD LCM 8MP Camera



NFC + QR







































## **SPECIFICATIONS**

Android 11			
Quad-Core 4*A53@2.0GHz			
RAM: 2GB + ROM: 16GB	RAM: 2GB + ROM: 16GB		
4G (LTE-FDD/LTE-TDD) + 3G (WCDMA) + 2G (G Wi-Fi 5: 2.4&5GHz, Bluetooth 5.0/BLE	4G (LTE-FDD/LTE-TDD) + 3G (WCDMA) + 2G (GSM), Wi-Fi 5: 2.4&5GHz, Bluetooth 5.0/BLE		
GPS/A-GPS, GLONASS, BDS, Galileo	GPS/A-GPS, GLONASS, BDS, Galileo		
5.0 inch, HD IPS LCD, 1280*720Pixel, Multi-touch			
Rear: 8MP AF with Flash LED, Support 1D/2D barcode			
Thermal printer, Paper size: 58mm*40mm			
3.8V/4000mAh			
Power Key, Volume+/-Key			
1W			
13.56MHz, ISO/IEC 14443, ISO/IEC 18092, Type A&B, Felica, Mifare card			
SIM*2 + TF Card*1	SIM*2 + TF Card*1		
Type C*1(USB2.0, OTG ), 3.5mm Audio Jack*1	Type C*1(USB2.0, OTG ), 3.5mm Audio Jack*1		
Input: 100-240V AC, 50/60Hz 0.35A Output: 5.0V DC/2.0A			
197mm (L)*77mm (W)*52.6mm (H)			
323g			
Operating Temperature: -10°C ~ 50°C (14°F~122°F) Storage Temperature: -20°C ~ 70°C (-4°F~158°F) Relative Humidity: 5%-96% (Non-Condensing)			
Adapter*1, USB Cable(only charging)*1, Manual*1			
CE, ANRT, EAC, FAC, CB, BIS, WPC, DGM, UN38.3, MSDS, GSMA, Google GMS SafetyNet Compliance			
Fingerprint Cha Biometric fingerprint module 5V/2  Fiscal Mul USB OR UART POGO PIN Connector (Type C only charging) Type	c C (data/damping) rging Cradle A ti-function Dock Lite C*1, RJ45*1, RJ11*1, Type A*2 e C USB to RJ 45 Adapter	Screen Protector Hydrogel film Silicone Cover Customized colors POS Bracket Desktop bracket	
	Quad-Core 4*A53@2.0GHz  RAM: 2GB + ROM: 16GB  4G (LTE-FDD/LTE-TDD) + 3G (WCDMA) + 2G (GS Wi-Fi 5: 2.4&5GHz, Bluetooth 5.0/BLE  GPS/A-GPS, GLONASS, BDS, Galileo  5.0 inch, HD IPS LCD, 1280*720Pixel, Multi-touck  Rear: 8MP AF with Flash LED, Support 1D/2D II  Thermal printer, Paper size: 58mm*40mm  3.8V/4000mAh  Power Key, Volume+/-Key  1W  13.56MHz, ISO/IEC 14443, ISO/IEC 18092, Type  SIM*2 + TF Card*1  Type C*1(USB2.0, OTG), 3.5mm Audio Jack*1  Input: 100-240V AC, 50/60Hz 0.35A Output: 5  197mm (L)*77mm (W)*52.6mm (H)  323g  Operating Temperature: -10°C ~ 50°C (14°F~12: Storage Temperature: -20°C ~ 70°C (-4°F~158°I Relative Humidity: 5%-96% (Non-Condensing)  Adapter*1, USB Cable(only charging)*1, Manual CE, ANRT, EAC, FAC, CB, BIS, WPC, DGM, UN38 Google GMS SafetyNet Compliance  Card Slot USB SIM*1 + PSAM*1 Type  Fingerprint Chall Sime Charging Charging)  Biometric fingerprint module 5V/2  Fiscal Multi- USB OR UART POGO PIN Connector (Type C only charging)  Barcode Scann Module 100	Quad-Core 4*A53@2.0GHz  RAM: 2GB + ROM: 16GB  4G (LTE-FDD/LTE-TDD) + 3G (WCDMA) + 2G (GSM), Wi-Fi 5: 2.4&5GHz, Bluetooth 5.0/BLE  GPS/A-GPS, GLONASS, BDS, Galileo  5.0 inch, HD IPS LCD, 1280*720Pixel, Multi-touch  Rear: 8MP AF with Flash LED, Support 1D/2D barcode  Thermal printer, Paper size: 58mm*40mm  3.8V/4000mAh  Power Key, Volume+/-Key  1W  13.56MHz, ISO/IEC 14443, ISO/IEC 18092, Type A&B, Felica, Mifare card  SIM*2 + TF Card*1  Type C*1(USB2.0, OTG), 3.5mm Audio Jack*1  Input: 100-240V AC, 50/60Hz 0.35A Output: 5.0V DC/2.0A  197mm (L)*77mm (W)*52.6mm (H)  323g  Operating Temperature: -10°C ~ 50°C (14*F~122*F) Storage Temperature: -20°C ~ 70°C (-4*F~158*F) Relative Humidity: 5%-96% (Non-Condensing)  Adapter*1, USB Cable(only charging)*1, Manual*1  CE, ANRT, EAC, FAC, CB, BIS, WPC, DGM, UN38.3, MSDS, GSMA, Google GMS SafetyNet Compliance  Card Slot SIM*1 + PSAM*1  Fingerprint Eingerprint Eingerprint Fingerprint	

# **F100 Options and Accessories**









## **F100 FP** Fingerprint

Fingerprint	Semiconductor capacitive biometric fingerprint module	Fiscal
Physical	197mm (L)*77mm (W)*55.6mm (H)	Physical
Weight	327g	Weight

### F100 Fiscal

USB OR UART POGO PIN Connector (Type C only charging)

197mm (L)\*77mm (W)\*52.6mm (H)

342g

#### **Barcode Scanner**

Image Siz	ze	640*480 Pixels 1D&2D
Field of Vi	ew	34°(H)*27°(V)
Motion Toler	ances	Up to 25in(63.5cm) per second

