

Ð

F20

Smart Payment Terminal



Android 14

4G + 3G + 2G Wi-Fi 5: 2.4&5GHz BT 5.0

5.5" HD LCM 8MP + 2MP Cameras


踩

Retail

MSR + IC + NFC + QR

닐





励

Hotel

Pa

99

SPECIFICATIONS

Operating System	Android 14		
Processor	Quad-Core 4*A53@2.0GHz		
Memory	RAM: 2GB + ROM: 16GB		
Communications	4G (LTE-FDD/LTE-TDD) + 3G (WCDMA) + 2G (GSM), Wi-Fi 5: 2.4&5GHz, Bluetooth 5.0/BLE		
Location	GPS, BDS, Galileo, GLONASS, QZSS, SBAS		
Display	5.5 inch, HD IPS LCD, 1440*720 Pixel, Multi-touch		
Cameras	Rear: 8MP AF with Flash LED Front: 2MP FF Support 1D/2D barcode		
Printer	High-speed thermal printer, Paper size: 58mm*40mm		
Battery	7.6V/2500mAh (Equal to 3.8V/5000mAh)		
Magnetic Card Reader	ISO/IEC 7811, ISO/IEC 7813, Track 1/2/3, Bi-directional swiping		
IC Card Reader	ISO/IEC 7816, Conform to EMV L1/L2		
NFC	13.56MHz, ISO/IEC 14443, ISO18092, Type A&B, Felica, Mifare card		
Card Slot	SIM*2 + PSAM*1		
Peripheral Ports	Type C*1 (USB2.0, OTG)		
Adapter	Input: 100-240V AC, 50/60Hz 0.35A Output: 5V DC/2.0A		
Physical	212.6mm (L)*79.1mm (W)*51.9mm (H)		
Weight	427g	427g	
Environment	Operating Temperature: -10°C ~ 50°C (14°F~122°F) Storage Temperature: -20°C ~ 70°C (-4°F~158°F) Relative Humidity: 5%-96% (Non-Condensing)		
Accessories	Adapter*1, USB Cable(only charging)*1, Manual*1		
Certifications	PCI, EMV L1&L2, EMV Contactless L1, Paypass, PayWave, Amex, Discover, JCB, Pure, qUICS, Rupay, NSICC, TQM, CPACE, AuspayNET, EFT POS, INTERAC, NAPAS, RoHS, CE, FCC, PTCRB, EAC, BIS, ATEX, WEEE, CB, WPC, DGM, UN38.3, MSDS, NTRA-VOC, GSMA, Telec, JATE, ANRT, CMC, Google Smart Tap, RNIB, EAA		
	Camera Front Camera: None Rear Camera: 5MP/FF/AF, 2MP/FF	Fiscal USB OR UART POGO PIN Connector (Type C only charging)	Charging Cradle 5V/2A
	Sensor G-sensor	USB Cable Type C (data/damping)	Type C USB to RJ 45 Adapter 100 Mbps Ethernet LAN
Optional Items	TF-Card MicroSD (TF Max support 256GB) *1	Multi-function Battery Cover Type C*1, RJ45*1	Screen Protector Hydrogel film
	Card Slot SIM*1 + PSAM*2	Multi-function Dock Lite Type C*1, RJ45*1, RJ11*1, Type A*2	Silicone Cover Customized colors
	Fingerprint Biometric fingerprint module	Multi-function Dock Type C*1, RJ45*1, RJ11*1,	POS Bracket Desktop bracket
	(or PCBA that supports fingerprint function) Battery Options 7.6V/2750mAh (Equal to 3.8V/5500mAh)	Type A*2, Scanner*1	Cash Box Customized, 6V/1A

This document is provided to you for informational purposes only. All features and specifications are subject to change without notice. FEITIAN and the FEITIAN logo are either trademarks or registered trademarks of FEITIAN Technologies Co. Lid, in China and/or other countries. All other trademarks or brand names are the properties of their respective holders. © 2025 FEITIAN Technologies Co. Lid. All rights reserved.

F20 Options and Accessories



Semiconductor capacitive biometric fingerprint module

212.6mm (L)*79.1mm (W)*55.5mm (H)



F20 FP Fingerprint

430g

Fingerprint

Physical

Weight

F20 Fiscal

Fiscal		USB OR UART POGO PIN Connector (Type C only charging)	
Physica	al	212.6mm (L)*79.1mm (W)*51.9mm (H)	
Weight		440g	



Multi Dock

Ports	Type C*1, RJ45*1, RJ11*1, Type A*2, Scanner*1
Pogo Pin	8 pin
Certification	CE, RoHS



Multi Dock Lite

Ports	Type C*1, RJ45*1, RJ11*1, Type A*2
Pogo Pin	8 pin
Certification	CE, RoHS



Charging Cradle

Input	USB Type C 5V/2A
Pogo Pin	2 pin
Certification	CE, RoHS



Multi-function Battery Cover

Ports	Type C*1, RJ45*1
Pogo Pin	8 pin
Certification	CE, RoHS



This document is provided to you for informational purposes only. All features and specifications are subject to change without notice. FEITIAN and the FEITIAN logo are either trademarks or registered trademarks of FEITIAN Technologies Co., Ltd. in China and/or other countries All other trademarks or brand names are the properties of their respective holders. © 2025 FEITIAN Technologies Co., Ltd. All rights reserved.