

F360 Payment Android POS



reddot winner 2024



F360 Accessories



F360 Unattended



F360 Multi Dock(Charging+Printer)



F360 Customer Display+Printer



F360 Sound Dock



F360 Mini-Unattended

SPECIFICATIONS

Operating System	Android 13
Processor	Quad-Core 4*A53@2.0GHz
Memory	2GB RAM + 16GB ROM
Communications	4G + 3G + 2G, Wi-Fi 5: 2.4&5GHz, Bluetooth 5.0/BLE
Location	GPS, BDS, Galileo, GLONASS, QZSS, SBAS
Display	3.2 inch, IPS LCD, 240*320 Pixel, Two Point-touch
Camera	Front: 0.3MP FF, Support 1D/2D barcode
Battery	3.7V/2000mAh
IC Card Reader	ISO/IEC 7816, Conform to EMV L1/L2
NFC	13.56MHz, ISO/IEC 14443, ISO/IEC 18092, Type A&B, Felica, Mifare card
Key/Button	Power Key
Light Strip	Three-color Light, Customizable color
Audio	1W
Card Type	Nano SIM*1 + PSAM*1 (Optional: eSIM*1 + SIM*1 + PSAM*1)
Peripheral Ports	Type C*1 (USB2.0, OTG), Pogopin*1(8PIN)
Adapter	Input: 100-240V AC, 50/60Hz 0.35A Output: 5V DC/2.0A
Physical/Weight	Φ98.5mm*22.9mm (H)/186.6g
Environment	Operating Temperature: -10°C ~ 50°C (14°F~122°F) Storage Temperature: -20°C ~ 70°C (-4°F~158°F) Relative Humidity: 5%-96% (Non-Condensing)
Accessories	Adapter*1, USB Cable (only charging)*1, Manual*1
Certifications	PCI, EMV L1/L2, EMV Contactless L1, PayWave, Paypass, Pure, Amex, Discover, qUICS, JCB, AuspayNET, MIR, EFT POS, Felica, Interac, NSICCS, RUPAY, RoHS, TQM, CE, FCC, MIC, JATE, ANRT, CMC,BIS, WPC, NTRA-VOC, WEEE, GSMA, CB, DGM, UN38.3, MSDS, RNIB, IC ID, Verizon

F360 Accessories



F360-2 Unattended

Card Type	Nano SIM*1 + PSAM*1
Interface	RS232-A*1(RJ45), RS232-B*1(RJ45), LAN*1(RJ45), PWRDIG.I/O*1, MDB-M EXE*1, MDB-S*1, 4G SMA*1, Type A*1, Type C*1(USB2.0, OTG)
Adapter	Input: 100-240V AC, 50/60Hz 0.35A Output: 12V-48V DC/2.0A
Physical	134mm(L)*134mm(W)*60mm(H)
Weight	496.5g

F360-3 Multi Dock(Charging+Printer)

Interface	RJ11*1(Cash Drawer), DC Jack*1(Charging), RJ45*1(LAN 100M), Type A*1(USB 2.0 OTG), Type B*1(RS232), Pogopin*1(8PIN)
WiFi/BT	Wi-Fi 4, Bluetooth 5.0/BLE
Keys/Buttons	Power Key, Volume+/- Key, Function Key
Audio	4Ω3W
Adapter	Input: 100-240V AC, 50/60Hz 0.35A Output: 12V DC/3.0A
Accessories	Adapter*1, Manual*1

Printer Module

Printing Method	Thermal dot printing
Number of Dots	384 dots/line
Resolution	8 dots/mm(203 dpi)
Paper Size	58mm*60mm
Max Printing Speed	80 mm/s
Physical/Weight	146mm(L)*125mm(W)*105mm(H)/349g



F360-4 Customer Display+Printer Dock

Interface	RJ11*1(Cash Drawer), DC Jack*1(Charging), RJ45*1(LAN 100M), Type A*1(USB 2.0 OTG), Type B*1(RS232), Pogopin*1(8PIN)
WiFi /BT	Wi-Fi 4, Bluetooth 5.0/BLE
Print Size	58mm*60mm
Max Printing Speed	80mm/s
Audio	4Ω3W
Customer Display	2.4inch, 240*320 IPS
Adapter	Input: 100-240V AC, 50/60Hz 0.35A Output: 12V DC/3.0A

F360-5 Sound Dock

Interface	Type C*1
Audio	4Ω3W
Adapter	Input: 100-240V AC, 50/60Hz 0.35A Output: 5.0V DC/2.0A



F360-7 Mini-Unattended

Interface	COIN(4PIN), MAINBOARD(4PIN), Uart(5PIN), FUNCTION(5PIN), SPK(2PIN), Type A*1, Type C*1(USB2.0, OTG)
Card Type	Nano SIM *1+Nano PSAM* 1
Adapter	Input: 100-240V AC, 50/60Hz 0.35A Output: 5V-24V DC/2.0A
Accessorie	Manual*1
Physical	110mm(L)*110mm(W)*39mm(H)

